SANDPIPER EVOLUTION X 1 1/2” NON-METALLIC PUMP TECHNICAL DATA SHEET



MODEL SPE15

STANDARD DUTY NON-METALLIC BALL VALVE PUMP

Patent Pending, High Performance AODD

PERFORMANCE

SUCTION / DISCHARGE PORT SIZE

- 1 1/2” ANSI/DIN Flange

CAPACITY

- 0 to 135 GPM (0 to 511 LPM)

AIR DISTRIBUTION VALVE

- No-lube, no-stall design

SOLIDS-HANDLING

- Up to .5 in. (12mm)

SUCTION LIFT

- 21.9’ (6.7 m) Dry

HEADS UP TO

- 125 psi or 288 ft. of water (8.6 bar or 88 meters)

MAXIMUM OPERATING PRESSURE


- 125 psi (8.6 bar)

DISPLACEMENT/STROKE

- 0.78 Gallon / 2.95 Liter

PUMP WEIGHTS

- Polypropylene 60 lbs. (27 kg)
- PVDF 86 lbs. (39 kg)
- Conductive Polypropylene 64 lbs. (29 kg)



5 YEAR LIMITED PRODUCT WARRANTY

5 Year Guarantee for defects in material or workmanship. See sandpiperpump.com/content/warranty-certifications for complete warranty, including terms and conditions, limitations and exclusions.

USE ONLY GENUINE SANDPIPER PARTS

All certification, standards, guarantees & warranties originally supplied with this pump will be invalidated by the use of service parts not identified as “Genuine SANDPIPER Parts.”

SANDPIPER®
SANDPIPERPUMP.COM


Warren Rupp, Inc. • A Unit of IDEX Corporation
800 N. Main St., Mansfield, Ohio 44902 USA
Telephone 419.524.8388 • Fax 419.522.7867


ISO 9001 Certified
ISO 14001 Certified

DIMENSIONS

SPE15 Non-Metallic Center Ported Options

Dimensions in inches (metric dimensions in brackets). Dimensional Tolerance .125" (3mm).





NOTES

1. SUCTION AND DISCHARGE PORT FLANGES ARE DESIGNED TO FIT BOTH ANSI 125# CONNECTION AND PN10 50mm DIN CONNECTION
2. DISCHARGE PORT CAN BE ROTATED 90° HORIZONTAL
3. 1" FNPT EXHAUST PORT FOR THREADED MUFFLER OR PIPING EXHAUST AIR IN SUBMERGED APPLICATIONS

SANDPIPER®
SANDPIPERPUMP.COM
Warren Rupp, Inc. • A Unit of IDEX Corporation
800 N. Main St., Mansfield, Ohio 44902 USA
Telephone 419.524.8388 • Fax 419.522.7867

EXPLANATION OF PUMP NOMENCLATURE

Your Model #: SP E 15 B _ _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

(fill in from pump nameplate)

Position.....	P1	P2	P3	P4	P5	P6	P7	P8	P9	P10	P11	P12	P13	P14	P15	P16
	Pump Brand	Product Line	Pump Size	Check Valve Type	Wetted Material	Non-Wetted Material	Diaphragm Material	Backup Diaphragm	Check Valve Material	Seat Material	Air Valve	Air Valve Option	Exhaust Option	Port Type	Port Option	Design Level

PUMP BRAND
SP SANDPIPER

PRODUCT LINE
E Evolution

PUMP SIZE
15 1 1/2"

CHECK VALVE TYPE
B Ball

WET END MATERIALS
C Conductive Polypropylene
K PVDF (Kynar)
P Polypropylene

NON-WETTED MATERIAL
C Conductive Polypropylene
P Polypropylene

DIAPHRAGM MATERIAL
B Nitrile (Buna)
N Neoprene
R Santoprene
T PTFE Overlay
V FKM (Viton)
Z One Piece Bonded PTFE

*BACKUP DIAPHRAGM
B Nitrile (Buna)
N Neoprene
R Santoprene
0 None

CHECK VALVE MATERIAL
B Nitrile
N Neoprene
R Santoprene
T PTFE

SEAT MATERIAL
K PVDF (Kynar)
P Polypropylene

AIR VALVE
0 SANDPIPER Standard

AIR VALVE OPTION
0 Matched ground sleeve and spool
B Stainless / Brass sleeve & spool set
**S Stainless / Brass sleeve & spool set - Aluminum free pump

EXHAUST OPTION
6 Threaded Muffler (Conductive)

PORT TYPE
U Universal ANSI/DIN Flange

PORT Option
C Center Ported

DESIGN LEVEL
1 Design Level

*If T is selected for Diaphragm Material, select backup diaphragm "N or R"
*If Z is selected for Diaphragm Material, the backup will be "B"
*For all other Diaphragm Materials, the backup will be "0"
**Pumps with stainless brass sleeve and spool main air valve option, do not contain Aluminum. Equipped with stainless steel pilot sleeve and inner diaphragm plate.

MATERIALS

Material Profile:	Operating Temperatures:	
⚠ CAUTION! Operating temperature limitations are as follows:	Max.	Min.
CONDUCTIVE ACETAL: Tough, impact resistant, ductile. Good abrasion resistance and low friction surface. Generally inert, with good chemical resistance except for strong acids and oxidizing agents.	190°F 88°C	-20°F -29°C
EPDM: Shows very good water and chemical resistance. Has poor resistance to oils and solvents, but is fair in ketones and alcohols.	280°F 138°C	-40°F -40°C
FKM (FLUOROCARBON): Shows good resistance to a wide range of oils and solvents; especially all aliphatic, aromatic and halogenated hydrocarbons, acids, animal and vegetable oils. Hot water or hot aqueous solutions (over 70°F(21°C)) will attack FKM.	350°F 177°C	-40°F -40°C
HYTREL®: Good on acids, bases, amines and glycols at room temperatures only.	220°F 104°C	-20°F -29°C
NEOPRENE: All purpose. Resistance to vegetable oils. Generally not affected by moderate chemicals, fats, greases and many oils and solvents. Generally attacked by strong oxidizing acids, ketones, esters and nitro hydrocarbons and chlorinated aromatic hydrocarbons.	200°F 93°C	-10°F -23°C
NITRILE: General purpose, oil-resistant. Shows good solvent, oil, water and hydraulic fluid resistance. Should not be used with highly polar solvents like acetone and MEK, ozone, chlorinated hydrocarbons and nitro hydrocarbons.	190°F 88°C	-10°F -23°C
NYLON: 6/6 High strength and toughness over a wide temperature range. Moderate to good resistance to fuels, oils and chemicals.	180°F 82°C	32°F 0°C
POLYPROPYLENE: A thermoplastic polymer. Moderate tensile and flex strength. Resists stong acids and alkali. Attacked by chlorine, fuming nitric acid and other strong oxidizing agents.	180°F 82°C	32°F 0°C
PVDF: (Polyvinylidene Fluoride) A durable fluoroplastic with excellent chemical resistance. Excellent for UV applications. High tensile strength and impact resistance.	250°F 121°C	0°F -18°C
SANTOPRENE®: Injection molded thermoplastic elastomer with no fabric layer. Long mechanical flex life. Excellent abrasion resistance.	275°F 135°C	-40°F -40°C
UHMW PE: A thermoplastic that is highly resistant to a broad range of chemicals. Exhibits outstanding abrasion and impact resistance, along with environmental stress-cracking resistance.	180°F 82°C	-35°F -37°C
URETHANE: Shows good resistance to abrasives. Has poor resistance to most solvents and oils.	150°F 66°C	32°F 0°C
VIRGIN PTFE: (PFA/TFE) Chemically inert, virtually impervious. Very few chemicals are known to chemically react with PTFE; molten alkali metals, turbulent liquid or gaseous fluorine and a few fluoro-chemicals such as chlorine trifluoride or oxygen difluoride which readily liberate free fluorine at elevated temperatures.	220°F 104°C	-35°F -37°C

Maximum and Minimum Temperatures are the limits for which these materials can be operated. Temperatures coupled with pressure affect the longevity of diaphragm pump components. Maximum life should not be expected at the extreme limits of the temperature ranges.

Metals:

ALLOY C: Equal to ASTM494 CW-12M-1 specification for nickel and nickel alloy.

STAINLESS STEEL: Equal to or exceeding ASTM specification A743 CF-8M for corrosion resistant iron chromium, iron chromium nickel and nickel based alloy castings for general applications. Commonly referred to as 316 Stainless Steel in the pump industry.

For specific applications, always consult the Chemical Resistance Chart.

NOTE: See service manual for ATEX details.

SANDPIPER®
SANDPIPERPUMP.COM
Warren Rupp, Inc. • A Unit of IDEX Corporation
800 N. Main St., Mansfield, Ohio 44902 USA
Telephone 419.524.8388 • Fax 419.522.7867